



Closed-loop recycling of fibre-reinforced plastic composites

IP ref: [2019-064]

Energy and Clean Technology

Problem

- The ultra-high strength in lightweight carbon fibre reinforced composites (CFRP) originates from the alignment of the individual carbon fibrils.
- Upon recycling of the composite from its high-performance applications, these individual carbon fibrils become misaligned and are not easily realigned.
- The lack of methods to effectively realign waste and recycled carbon fibre filaments severely limits the feasibility and circularity of fibre-reinforced plastic recycling.

Technology

We have developed a hydromagnetic fibre alignment machine (HMFAM) that realigns carbon fibre and enables the remanufacturing of recycled composites.

Using this device, we are able to control the fibre length, fibre content, geometry and surface characteristics during the realignment process of recycled fibres, with comparatively high fibre volume fractions up to 60%.

Re-manufactured CFRP composites using the recycled carbon fibres have shown mechanical properties of up to 50% of a composite with pristine fibres, which is as strong as steel.

Inventors

This technology was developed by Dr. Ali Hadigheh.



Prototype alignment device

Commercial Opportunity

This technology is a significant advance in the viability of fibre-reinforced plastic recycling, which may open-up new opportunities in areas including:

- Recycled CFRP composites for wind turbine, automotive, aerospace, sporting equipment, mining and defense parts
- Carbon fibre-reinforced construction materials
- Carbon fibre 3D printing filaments
- Recycled carbon fibre consumer products

Technology development stage



Intellectual Property Status

PCT application No. PCT/AU2021/050286.
National Phase Entry in AU, EP, KR, NZ, US.



Contact Us

Mark Berlage

Commercial Theme Leader
Mark.berlage@Sydney.edu.au
T: +61 407 407 327

Commercialisation Office
The University of Sydney
T: +61 2 9351 4000
Sydney.edu.au/cdip